


SAK Series
Q 10 AKZ4SS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com


Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | |
|------------|--|
| Type | Q 10 AKZ4SS |
| Order No. | 0369300000 |
| Version | SAK Series, Cross-connector, for cross-connection link, No. of poles: 10 |
| GTIN (EAN) | 4008190065744 |
| Qty. | 20 pc(s). |

**SAK Series
Q 10 AKZ4SS**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|---------|-----------------|------------|
| Width | 59.9 mm | Width (inches) | 2.358 inch |
| Height | 4 mm | Height (inches) | 0.157 inch |
| Depth | 13 mm | Depth (inches) | 0.512 inch |
| Net weight | 10.6 g | | |

Material data

| | | | |
|----------|-------|--------|------|
| Material | Cu Zn | Colour | Grey |
|----------|-------|--------|------|

System specifications

| | | | |
|---------------|---------------------------|-------------------------------------|--------------|
| Version | for cross-connection link | Tightening torque (cross-connector) | 0.4...0.8 Nm |
| Mounting rail | none | | |

Additional technical data

| | | | |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | Screwed | | |

Dimensions

| | |
|-----------------|--------|
| Pitch in mm (P) | 5.1 mm |
|-----------------|--------|

Rating data

| | |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000489 | ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 | ETIM 6.0 | EC000489 |
| UNSPSC | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 | | |

Product information

| | |
|------------------------------|--|
| Descriptive text accessories | Q2-Q10 AKZ 4SS, can also be used for AK 4 and AKZ 4 ST versions. |
|------------------------------|--|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|--|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |