

VG 11-SS 68 KB 5-10**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



This cable gland series is made from stainless steel and is well suited for industrial applications requiring IP68 protection. Its excellent resistance against seawater and impacts make it ideal for use in harsh conditions.

General ordering data

Type	VG 11-SS 68 KB 5-10
Order No.	1009760000
Version	Cable gland, PG 11, 6 mm, OD min. 5.00 - OD max. 10.00 mm, Stainless steel 1.4305 (303)
GTIN (EAN)	4032248714483
Qty.	50 pc(s).

VG 11-SS 68 KB 5-10

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Length	31.5 mm	Length (inches)	1.24 inch
Net weight	32 g		

General information

AF size 1	22 mm	AF size 2	22 mm
Cable gland	PG	Clamp insert	Polyamide 6
External thread	PG 11	Length of thread	6 mm
Material	Stainless steel 1.4305 (303)	O-Ring	NBR
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Outer cable diameter, max.	10 mm	Outer cable diameter, min.	5 mm
Protection degree	IP69K, IP68 - 5 bar (30 min.)	Seal insert	CR
Torque for cap nut, max.	13 Nm	Torque for cap nut, min.	10 Nm
Torque for connecting adapter, max.	15 Nm	Torque for connecting adapter, min.	20 Nm

Classifications

ETIM 4.0	EC002625	ETIM 5.0	EC002625
ETIM 6.0	EC000441	eClass 6.2	27-18-92-34
eClass 7.1	27-18-92-34	eClass 8.1	27-18-92-34
eClass 9.0	27-18-92-34	eClass 9.1	27-14-44-32

Product information

Descriptive text ordering data	1.4404 (316L) on request
--------------------------------	--------------------------

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN_WSCAD