

**VG 21-SS 68 KB 13-18****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



This cable gland series is made from stainless steel and is well suited for industrial applications requiring IP68 protection. Its excellent resistance against seawater and impacts make it ideal for use in harsh conditions.

**General ordering data**

Type	VG 21-SS 68 KB 13-18
Order No.	<a href="#">1009790000</a>
Version	Cable gland, PG 21, 7.2 mm, OD min. 13.00 - OD max. 18.00 mm, Stainless steel 1.4305 (303)
GTIN (EAN)	4032248714612
Qty.	25 pc(s).

## VG 21-SS 68 KB 13-18

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

## Technical data

## Dimensions and weights

Length	39.7 mm	Length (inches)	1.563 inch
Net weight	53.4 g		

## General information

AF size 1	30 mm	AF size 2	30 mm
Cable gland	PG	Clamp insert	Polyamide 6
External thread	PG 21	Length of thread	7.2 mm
Material	Stainless steel 1.4305 (303)	O-Ring	NBR
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Outer cable diameter, max.	18 mm	Outer cable diameter, min.	13 mm
Protection degree	IP69K, IP68 - 5 bar (30 min.)	Seal insert	CR
Torque for cap nut, max.	35 Nm	Torque for cap nut, min.	28 Nm
Torque for connecting adapter, max.	40 Nm	Torque for connecting adapter, min.	50 Nm

## Classifications

ETIM 4.0	EC002625	ETIM 5.0	EC002625
ETIM 6.0	EC000441	eClass 6.2	27-18-92-34
eClass 7.1	27-18-92-34	eClass 8.1	27-18-92-34
eClass 9.0	27-18-92-34	eClass 9.1	27-14-44-32

## Product information

Descriptive text ordering data	1.4404 (316L) on request
--------------------------------	--------------------------

## Approvals

Approvals



ROHS	Conform
------	---------

## Downloads

Brochure/Catalogue	<a href="#">CAT 3 HDC 17/18 EN</a> <a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN_WSCAD</a>