

**PAC  
PAC-UNIV-HE40-FD1-2M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



In comparison to conventional point-to-point cabling, the new PLC (FAD) front adapters combined with the passive (RSF PLC) and the active (RSF PLC) interfaces offer an improved, more efficient method of field wiring.

PLC (FAD) front adapters are connected to the PLC and to a standard cable which is connected to the interface or the MICROSERIES relay.

**General ordering data**

|            |  |
|------------|--|
| Type       | PAC-UNIV-HE40-FD1-2M                                       |
| Order No.  | <a href="#">7789808020</a>                                 |
| Version    | Pre-assembled cable, PAC, Cable LiYY, 0.25 mm <sup>2</sup> |
| GTIN (EAN) | 4032248217656  |
| Qty.       | 1 Stück  |

## PAC PAC-UNIV-HE40-FD1-2M

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Net weight 408 g

### Temperatures

Operating temperature -10...50 °C Storage temperature -10...60 °C

### General Data

|                       |            |                     |                      |
|-----------------------|------------|---------------------|----------------------|
| Connector PLC side    | HE10 40P   | Interface connector | HE10 40P             |
| Number of poles, min. | 40-pole    | Outer diameter      | 11.7 ± 1 mm          |
| Cable                 | Cable LiYY | Cable length        | 2 m                  |
| Material              | PVC        | Wire cross-section  | 0.25 mm <sup>2</sup> |

### Electrical Data

|                      |                     |   |           |
|----------------------|---------------------|---|-----------|
| Rated voltage (text) | ≤ 60 V DC ≤ 25 V AC | Permissible current strength per path, max. | 1 A       |
| Total current, max.  | 3 A                 | Resistance                                  | ≤ 80 mΩ/m |
| High voltage test    | 1 KV/1s             |   |           |

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 4.0   | EC000237    | ETIM 5.0   | EC000237    |
| ETIM 6.0   | EC000237    | eClass 6.2 | 27-24-92-05 |
| eClass 7.1 | 27-24-92-05 | eClass 9.0 | 27-24-22-20 |
| eClass 9.1 | 27-24-22-20 |            |             |

### Approvals

ROHS Conform